

SHIP STABILITY IN PRACTICE

CONTENTS:

| FOREWORD | | |
|----------|---|--|
| PART | 1 | |
| 1. | SHIP GEOMETRY | |
| | RECOMMENDED INTACTOSTABILITIES ORTHODICS OF SHIPSEN GASED IN GANCHOFF INCLUDING | |
| 1.1 | SHIP TYPES ACCORDING TO MEANS OF PHYSICAL SUPPORT | |
| 1.2 | HULL FORMS | |
| 1.2.1 | SHIP COORDINATE SYSTEM | |
| 1.2.2 | GRAPHIC DESCRIPTION OF HULL FORMS | |
| 1.3 | MAIN DIMENSIONS | |
| 1.4 | COEFFICIENTS OF FORM | 24 |
| 2. | FLOTABILITY | 25 |
| 2.1 | ARCHIMEDES' PRINCIPLE AND SHIP EQUILIBRIUM | |
| 2.2 | SHIP MASS AND CENTRE OF GRAVITY | 27 |
| 2.3 | IN SERVICE INCLINING TEST SYSTEM (ISITS) | 32 |
| 2.4 | DEADWEIGHT AND CARGO DEADWEIGHT | |
| 2.5 | MEAN THEORETICAL DRAUGHT "DH" | 35 |
| 2.6 | DRAUGHT MARKS | |
| 2.7 | FREEBOARD AND LOAD LINE MARK | The state of the s |
| 2.8 | TERMS AND DIMENSIONS RELATED TO THE LOAD LINES CONVENTION | |
| 2.9 | FREEBOARD PLAN | |
| 2.10 | CAPACITY PLAN | 50 |
| 3. | INTACT STABILITY | 52 |
| 3.1 | DEFINITION OF STABILITY | 52 |
| 3.2 | INITIAL TRANSVERSE METACENTRE "M" AND METACENTRIC HEIGHT "GM" | |
| 3.3 | METACENTRIC DIAGRAM | |
| 3.4 | RIGHTING ARM GZ | |
| 3.5 | CURVE OF STATICAL STABILITY | |
| 3.6 | CROSS CURVES OF STABILITY | |
| 3.7 | LOLL | |
| 3.8 | DESIGN FACTORS AFFECTING THE SHAPE OF THE GZ CURVE | 61 |
| 3.8.1 | ANGLE OF DECK IMMERSION | |
| 3.8.2 | DEPTH D | |
| 3.8.3 | MAXIMUM DRAUGHT | |
| 3.8.4 | BREADTH B | |
| 3.9 | OPERATIONAL FACTORS AFFECTING SHIP STABILITY | |
| 3.9.1 | LIST | |
| 3.9.2 | FREE SURFACE EFFECT | |
| 3.9.3 | HANGING LOADS | 73 |
| 3.9.4 | DRY BULK CARGOES | 73 |
| 3.9.5 | BULK CARGO LIQUEFACTION | |
| 3.9.6 | ICING | 75 |
| 3.10 | ANGLES OF DOWNFLOODING | 76 |
| 3.11 | WIND HEELING ARM | |
| 3.12 | INTERNATIONAL CODE ON INTACT STABILITY 2008 (2008 IS CODE) | |
| 3.12.1 | INTRODUCTION | |
| 3.12.2 | PURPOSE | |
| 3.12.3 | DEFINITIONS | |
| 3.12.4 | PART A - MANDATORY STABILITY CRITERIA | |
| 3.12.5 | PART B - RECOMMENDATIONS FOR SHIPS ENGAGED IN CERTAIN TYPES OF OPERATIONS | |
| 3.13 | GENERAL INTACT STABILITY CRITERIA | |
| 3.14 | MINIMUM OPERATIONAL METACENTRIC HEIGHT GM _{MIN} CURVE | |
| 3.15 | MAXIMUM PERMISSIBLE VCG _{MAX} CURVE | 94 |

SHIP STABILITY IN PRACTICE

| 3.16 | STABILITY DURING HEAVY LIFT OPERATIONS | |
|--------|--|-----------|
| 3.17 | RECOMMENDED INTACT STABILITY CRITERIA FOR FISHING VESSELS | 103 |
| 3.18 | RECOMMENDED INTACT STABILITY CRITERIA FOR OFFSHORE SUPPLY VESSELS (PSV) | 106 |
| 3.19 | ANCHOR HANDLING OPERATIONS | 107 |
| 3.19.1 | ANCHOR HANDLING TUG SUPPLY VESSELS | 107 |
| 3.19.2 | ANCHOR HANDLING OPERATIONS | 108 |
| 3.19.3 | RECOMMENDED INTACT STABILITY CRITERIA FOR SHIPS ENGAGED IN ANCHOR | 110 |
| | HANDLING OPERATIONS (ACC. TO IS CODE 2008, PART B, CHAPTER 2, PARAGRAPH 2.7) | 110 |
| 3.20 | TUGS | 114 |
| 3.20.1 | PRIMARY FUNCTIONS | |
| 3.20.2 | TUG STABILITY, DESIGN AND MANOEUVRING CONSIDERATIONS | 118 |
| 3.20.3 | RECOMMENDED INTACT STABILITY CRITERIA FOR SHIPS ENGAGED | 100 |
| | IN TOWING AND ESCORT OPERATIONS | 122 |
| 4. | DANGEROUS SITUATIONS IN ADVERSE WEATHER AND SEA CONDITIONS | 127 |
| 4.0 | INTRODUCTION | 127 |
| 4.0 | WAVES PARAMETERS | 128 |
| 4.2 | PHENOMENA OCCURING IN FOLLOWING AND QUARTERING SEAS | 129 |
| 4.2.1 | SURF-RIDING AND BROACHING-TO PHENOMENON | 129 |
| 4.2.2 | REDUCTION OF STABILITY IN LONGITUDINAL WAVES | 130 |
| 4.3 | SYNCHRONOUS ROLLING MOTION | 130 |
| 4.4 | PARAMETRIC ROLL RESONANCE | 130 |
| 4.5 | SUCCESSIVE HIGH-WAVE ATTACKS | 134 |
| 4.6 | OTHER HAZARDS AND RISKS | 134 |
| 5. | CAPSIZING | 135 |
| 5.0 | GENERAL | 135 |
| 5.1 | CASE STUDIES | 135 |
| 5.1.1 | CAPSIZING OF THE CONTAINER SHIP DONGEDIJK | |
| | (ACCORDING TO THE CASUALTY REPORT) | 135 |
| 5.1.2 | CAPSIZING OF THE MPV ANGELN | 136 |
| 5.1.3 | CAPSIZING OF THE CONTAINER VESSEL DENEB | 138 |
| 5.1.4 | CAPSIZING OF THE HEAVY LIFT SHIP STELLAMARE | |
| | (ACCORDING TO THE CASUALTY REPORT) | 140 |
| 5.1.5 | CAPSIZING OF THE ANCHOR HANDLING TUG STEVNS POWER | 140 |
| 5.1.6 | CAPSIZING AND SINKING OF THE BOURBON DOLPHIN | 1.8.8 |
| | (ACCORDING TO SAFETY4SEA) | 141 |
| 5.1.7 | COLLISION AND CAPSIZING OF TUG FAIRPLAY 22 | 143 |
| 6. | SUBDIVISION AND DAMAGE STABILITY OF SHIPS | 145 |
| 6.0 | INTRODUCTION | 145 |
| 6.1 | HULL WATERTIGHT SUBDIVISION | |
| 6.2 | SHIP COLLISIONS | 149 |
| 6.3 | CASE STUDIES OF STRUCTURAL FAILURES, GROUDINGS AND COLLISIONS | |
| 6.3.1 | CATASTROPHIC STRUCTURAL FAILURE OF THE ORE CARRIER STELLAR DAISY | |
| 6.3.2 | GROUNDING AND SCUTTLING OF THE ORE CARRIER STELLA BANNER | 151 |
| 6.3.3 | GROUNDING AND TOTAL LOSS OF THE CRUISE SHIP COSTA CONCORDIA | 152 |
| 6.3.4 | ROCKNES - CAPSIZING AFTER GROUNDING | 154 |
| | (ACCORDING TO THE INVESTIGATION REPORT) | 154 |
| 6.3.5 | COLLISION OF THE SMALL COASTER JOANNA WITH THE RO-RO FERRY STENA NAUTICA | 155 |
| 6.3.6 | FOUNDERING OF THE 70,000DWT BULK CARRIER FU SHAN HAI STRUCK | 3 1 3 5 1 |
| 0.5.0 | BY THE 5200DWT MULTI-PURPOSE | 156 |
| 6.3.7 | COLLISION AND TOTAL LOSS OF THE MPV FLINTERSTAR | 158 |
| 6.4 | BILGED VESSEL | 159 |
| 6.5 | REGULATIONS FOR SUBDIVISION AND DAMAGE STABILITY | 162 |
| | | |

SHIP STABILITY IN PRACTICE

| 6.5.1 | INTRODUCTION | |
|---------|---|--------|
| 6.5.2 | SOLAS 2020 DAMAGE STABILITY REGULATIONS (PROBABILISTIC CONCEPT) | 162 |
| 6.5.3 | SUBDIVISION AND DAMAGE STABILITY OF MULTI-PURPOSE VESSELS | |
| 6.5.4 | SUBDIVISION AND DAMAGE STABILITY OF BULKERS | |
| 6.5.5 | SUBDIVISION AND DAMAGE STABILITY OF CONTAINER VESSELS | 175 |
| 6.5.6 | SUBDIVISION AND DAMAGE STABILITY OF RO-RO FREIGHTERS | 181 |
| 6.5.7 | SUBDIVISION AND DAMAGE STABILITY OF RORO PASSENGER VESSELS | 187 |
| 6.5.7.1 | PROBLEMS | 187 |
| 6.5.7.2 | FROM STOCKHOLM AGREEMENT TO SOLAS 2020 | 193 |
| 6.5.8 | SUBDIVISION AND DAMAGE STABILITY OF TANKERS | 196 |
| 6.5.8.1 | INTRODUCTION | 196 |
| 6.5.8.2 | DAMAGE STABILITY REQUIREMENTS | 198 |
| 6.5.8.3 | MARPOL ANNEX 1, REGULATION 28 - SUBDIVISION AND DAMAGE STABILITY | |
| 6.5.8.4 | DAMAGE STABILITY CRITERIA FOR OIL TANKERS | |
| | (MARPOL ANNEX 1 REGULATION 25 PARAGRAPH 3) | 202 |
| 6.5.8.5 | DIRECT STABILITY CALCULATIONS ON BOARD | |
| 6.6 | DESIGN FOR DAMAGE SURVIVABILITY | |
| 6.6.1 | PROTECTION OF THE ENGINE ROOM AGAINST FLOODING | |
| 6.6.2 | FOREPEAK | |
| 6.6.3 | SAFER BOWS | |
| 6.6.4 | LIMITING PROGRESSIVE FLOODING | |
| 6.6.5 | | |
| 0.0.5 | LOOKING FOR SAFER CAR CARRIERS | 212 |
| PART | 2 | 217 |
| 7. | ONBOARD STABILITY DOCUMENTATION | 218 |
| 7.0 | INTRODUCTION | 218 |
| 7.1 | SCOPE OF DOCUMENTATION | |
| 7.2 | ONBOARD INTACT STABILITY DOCUMENTATION | |
| 7.2.1 | LOADING AND STABILITY MANUAL (LSM) | |
| 7.2.2 | CARGO SPACE INFORMATION | |
| 7.2.3 | TANK SPACE INFORMATION | |
| 7.2.4 | HYDROSTATIC DATA TABLES | |
| 7.2.5 | CROSS CURVES OF STABILITY TABLES | |
| 7.3 | ONBOARD DAMAGE STABILITY DOCUMENTATION | |
| 7.3.1 | SUBDIVISION AND DAMAGE STABILITY CALCULATIONS | |
| 7.3.2 | DAMAGE CONTROL INFORMATION (DCI) | |
| 7.3.2.1 | DAMAGE CONTROL PLAN (DCP) | |
| | | |
| 7.3.2.2 | DAMAGE CONTROL MANUAL (DCM) EXTERNAL WATERTIGHT INTEGRITY PLAN (SEE ALSO FREEBOARD PLAN SECTION 2.9) | |
| | INTERNAL WATERTIGHT INTEGRITY PLAN (SEE ALSO FREEBOARD PLAN SECTION 2.9) | |
| 7.3.2.4 | | |
| PART 3 | APPENDICES ON | CD-ROM |
| 1. | FREEBOARD PLAN_BOOKLET | |
| 2. | CAPACITY PLAN & DEADWEIGHT SCALE_DRAWING | |
| 3. | MEDANGARA_CAPACITY PLAN_BOOKLET | |
| 4. | ARIADNA_TAP_DRAWING | |
| 5. | CATHERINE_TANKS_BOOKLET | |
| 6. | RORO FERRY_EXTRACTS FROM STABILITY INFORMATION | |
| 7. | TANKER_EXTRACTS FROM STABILITY INFORMATION | |
| 8. | AHTS_EXTRACTS FROM STABILITY INFORMATION | |
| 9. | ESCORT TUG_EXTRACTS FROM STABILITY INFORMATION | |
| 10. | LIVE FISH CARRIER_EXTRACTS FROM STABILITY INFORMATION | |
| 11. | CV5300TEU_DAMAGE CONTROL PLAN 1_DRAWING | |
| 12. | CV5300TEU_DAMAGE CONTROL PLAN 2_DRAWING | |
| 13. | MSC 1143 | |
| 14 | PLIRS LOSS PREVENTION THE AND TOW SAFETY AND OPERATIONAL GUIDE | |